

Astec Wallmaster Superwash Low Sheen

Astec Paints (Astec Paints Australasia)

Chemwatch Hazard Alert Code: 1

Chemwatch: **5359-97** Version No: **5.1**

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: **23/12/2022** Print Date: **23/01/2023** L.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Astec Wallmaster Superwash Low Sheen
Chemical Name	Not Applicable
Synonyms	Wallmaster Superwash Low Sheen Accent, Wallmaster Superwash Low Sheen Mid, Wallmaster Superwash Low Sheen White, WMSWLS
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Surface coating applied by brush, roller or spray.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Astec Paints (Astec Paints Australasia)		
Address	22-24 Pinn Street St Marys SA 5042 Australia		
Telephone	+61 8 8297 2000		
Fax	+61 8 8297 2555		
Website	http://www.astecpaints.com.au/		
Email	enquiries@astecpaints.com.au		

Emergency telephone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE	
Emergency telephone numbers	+61 1800 951 288	
Other emergency telephone numbers	+61 3 9573 3188	

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Chemwatch Hazard Ratings

	Min	Max	
Flammability	0		
Toxicity	1	1	
Body Contact	1 📕		0 = Minimum
Reactivity	0	1	2 = Moderate 3 = High 4 = Extreme
Chronic	1	1	

Poisons Schedule	Not Applicable
Classification [1]	Serious Eye Damage/Eye Irritation Category 2B

Legend:

Label elements

Hazard pictogram(s)	Not Applicable	
Signal word	Warning	

Hazard statement(s)

H320 Causes eye irritation.

Precautionary statement(s) Prevention

P264	Wash all exposed external body areas thoroughly after handling.
------	---

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available	30-60	acrylic copolymer, non-hazardous
13463-67-7	30-60	C.I. Pigment White 6
Not Available	20-35	inorganic micro filler, mixture, non-hazardous
Not Available	10-30	Ingredients determined not to be hazardous
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of

extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

- foam.
- dry chemical powder.
- carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known

Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers. Decomposes on heating and may produce toxic fumes of carbon monoxide (CO). May emit acrid smoke. Other decomposition products include: carbon dioxide (CO2)
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	 Minor hazard. Clear area of personnel. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal. Wash area and prevent runoff into drains or waterways. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

	5
Safe handling	 Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. When handling DO NOT eat, drink or smoke. Always wash hands with soap and water after handling. Avoid physical damage to containers. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS.

Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.
-------------------	---

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure	C.I. Pigment	Titanium	10	Not	Not	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Standards	White 6	dioxide	mg/m3	Available	Available	

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
C.I. Pigment White 6	30 mg/m3	330 mg/m3		2,000 mg/m3
Ingredient	Original IDLH		Revised IDLH	
C.I. Pigment White 6	5,000 mg/m3		Not Available	

MATERIAL DATA

Exposure controls

Appropriate engineering controls	General exhaust is adequate under normal operating conditions.
Personal protection	
Eye and face protection	 Safety glasses with side shields; or as required, Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: • Overalls. • Barrier cream. • Eyewash unit.

Respiratory protection

- + Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Information on basic physical and chemical properties

Appearance White or coloured viscous liquid; mixes with water.

Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	<60
Vapour pressure (kPa)	Negligible	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	<1

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by th damaging to the health of the individual.	e material during the course of normal handling, may be	
Ingestion	The material has NOT been classified by EC Directives or other of of the lack of corroborating animal or human evidence. The mate following ingestion, especially where pre-existing organ (e.g liver toxic substances are generally based on doses producing mortal Gastrointestinal tract discomfort may produce nausea and vomiti quantities is not thought to be cause for concern.	classification systems as "harmful by ingestion". This is because irial may still be damaging to the health of the individual, , kidney) damage is evident. Present definitions of harmful or ity rather than those producing morbidity (disease, ill-health). ng. In an occupational setting however, ingestion of insignificant	
Skin Contact	The material may cause skin irritation after prolonged or repeated This form of dermatitis is often characterised by skin redness (en intercellular oedema of the spongy layer (spongiosis) and intrace	d exposure and may produce a contact dermatitis (nonallergic). ythema) and swelling epidermis. Histologically there may be Ilular oedema of the epidermis.	
Eye	The material may be irritating to the eye, with prolonged contact irritants may produce conjunctivitis.	causing inflammation. Repeated or prolonged exposure to	
Chronic	Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.		
Astec Wallmaster Superwash Low Sheen	TOXICITY Not Available	IRRITATION Not Available	

	ΤΟΧΙΟΙΤΥ	IRRITATION		
C.I. Pigment White 6	dermal (hamster) LD50: >=10000 mg/kg ^[2]	Eye: no adverse	e effect observed (not irritating) ^[1]	
	Inhalation(Rat) LC50: >2.28 mg/l4h ^[1]	Skin (rabbit)		
	Oral (Rat) LD50: >=2000 mg/kg ^[1]	Skin: no adverse	e effect observed (not irritating) ^[1]	
Legend:	1. Value obtained from Europe ECHA Registered Unless otherwise specified data extracted from F	Substances - Acute toxicity 2. Va RTECS - Register of Toxic Effect of	lue obtained from manufacturer's SDS. f chemical Substances	
C.1. PIGMENT WHITE 6	Oral (Rat) LD50: >=2000 mg/kg ⁽¹⁾ Value obtained from Europe ECHA Registered Unless otherwise specified data extracted from R Substance has been investigated as a mutagen, t For titanium dioxide: Humans can be exposed to titanium dioxide via in titanium dioxide is poorly characterized relative to that are considered to affect deposition and retent summarized in the monograph on carbon black.) case reports that showed deposits of titanium dioxide. Stud healthy skin of human volunteers revealed that tit corneum, suggesting that healthy skin is an effect dioxide in compromised skin. Respiratory effects that have been observed amo pleural disease with plaques and pleural thickenin exposed to asbestos and/or silica. No data were available on genotoxic effects in tita Many data on deposition, retention and clearance route. Titanium dioxide inhalation studies showed lung, mass per body weight) and clearance kinetic clearance of titanium dioxide is also affected by p Differences in dose rate or clearance kinetics and the higher toxic and inflammatory lung responses studies with titanium dioxide have demonstrated t mediated clearance. Hamsters have the most effic dioxide are more slowly cleared than their fine con Titanium dioxide causes varying degrees of inflan cholesterol granulomas and fibrosis. Rodents exp particles compared with fine particles on a mass t area, and are considered to result from impaired p Fine titanium dioxide particle show minimal cytof alveolar macrophages in vitro at mass dose concentration with fine and ultrafine titanium dioxide and purified reactive oxygen species by both particle types. Th enhanced by exposure to simulated sunlight/ultrar Animal carcinogenicity data Pigmentary and ultrafine titanium dioxide were tear rats and female mice, by intratracheal administration in one inhalation study, the incidence of benign ar study, the incidences of lung adenomas were incr 	Skin: no adverse Substances - Acute toxicity 2. Va RTECS - Register of Toxic Effect of tumorigen and primary irritant. The adverse tion patterns of inhaled, poorly so With regard to inhaled titanium divide in lung tissue as well as in ly size-dependent absorption by the ies on the application of sunscree anium dioxide particles only pene tive barrier to titanium dioxide-exp anium dioxide-exposed humans. The of titanium dioxide in experiment d differences — both for normalize (cs — among rodent species inclu pre-exposure to gaseous pollutant the appearance of focal areas of to intratracheally instilled vs inha hat rodents experience dose-dep cient clearance of inhaled titanium unterparts. Inmation and associated pulmonar ereince stronger pulmonary effect pasis. These differences are relate obagocytosis and sequestration of toxicity to and inflammatory/pro-fil er particles. Ultrafine titanium diox a twhich this effect does not occ d DNA show induction of DNA dat his effect is stronger for ultrafine tit violet light.	e effect observed (not irritating) ⁽¹⁾ <i>Ilue obtained from manufacturer's SDS.</i> of chemical Substances tact. In human lungs, the clearance kinetic: eneral particle characteristics and host fact luble particles such as titanium dioxide are oxide, human data are mainly available from mph nodes. A single clinical study of oral gastrointestinal tract and large interindivid ens containing ultrafine titanium dioxide to trate into the outermost layers of the stratu ere are no studies on penetration of titanium loosed workers include decline in lung functi- vever, the workers in these studies were alse al animals are available for the inhalation ed pulmonary burden (deposited mass per- uding rats of different size, age and strain. is or co-exposure to cytotoxic aerosols. high particle burden have been implicated led titanium dioxide particles. Experimental endent impairment of alveolar macrophage in dioxide. Ultrafine primary particles of titar ry effects including lung epithelial cell injury ts after exposure to ultrafine titanium dioxide ed to lung burden in terms of particle surface f ultrafine particles into the interstitium. protic mediator release from primary human- ide particles inhibit phagocytosis of alveolar cur with fine titanium dioxide, and is markedly ministration in mice and rats, by inhalation and mice, by subcutaneous injection in rats creased in female rats. In another inhalatic male and female rats. Cystic keratinizing n-noplastic pulmonary keratinizing cysts w	
	also observed in the high-dose groups of female rats. Two inhalation studies in rats and one in female mice were negative. Intratracheally instilled female rats showed an increased incidence of both benign and malignant lung tumours following treatment with two types of titanium dioxide. Tumour incidence was not increased in intratracheally instilled hamsters and female			
	mice. In-vivo studies have shown enhanced micronucle intraperitoneally instilled mice. Increased Hprt mu rats. In another study, no enhanced oxidative DN/ with titanium dioxide. The results of most in-vitro of The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to huma Evidence of carcinogenicity may be inadequate of	us formation in bone marrow and tations were seen in lung epitheli A damage was observed in lung t genotoxicity studies with titanium ns. r limited in animal testing.	peripheral blood lymphocytes of al cells isolated from titanium dioxide-instill issues of rats that were intratracheally insti dioxide were negative.	
Acute Toxicity	×	Carcinogenicity	×	
Skin Irritation/Corrosion	×	Reproductivity	×	
Serious Eye Damage/Irritation	*	STOT - Single Exposure	×	

	Damage/initation
×	Respiratory or Skin sensitisation
×	Mutagenicity

Legend: X − Data either not available or does not fill the criteria for classification ✓ − Data available to make classification

×

×

STOT - Repeated Exposure

Aspiration Hazard

SECTION 12 Ecological information

Toxicity

A stas Mallmastar	Endpoint	Test Duration (hr)	Species	Value	Source
Astec Wallmaster Superwash Low Sheen	Not Available	Not Available	Not Available	Not Availat	Not ole Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1008h	Fish	<1.1-9.6	7
C.I. Pigment White 6	LC50	96h	Fish	1.85-3.06	ng/l 4
	EC50	72h	Algae or other aquatic plants	3.75-7.58	ng/l 4
	EC50	48h	Crustacea	1.9mg/l	2
	EC50	96h	Algae or other aquatic plants	179.05mg	/I 2
	NOEC(ECx)	504h	Crustacea	0.02mg/l	4
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
C.I. Pigment White 6	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
C.I. Pigment White 6	LOW (BCF = 10)

Mobility in soil

Ingredient	Mobility
C.I. Pigment White 6	LOW (KOC = 23.74)

SECTION 13 Disposal considerations

Waste treatment methods

	 Recycle wherever possible or consult manufacturer for recycling options.
Product / Packaging	Consult State Land Waste Management Authority for disposal.
disposal	Bury residue in an authorised landfill.
	Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
C.I. Pigment White 6	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
C.I. Pigment White 6	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

C.I. Pigment White 6 is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (C.I. Pigment White 6)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	23/12/2022
Initial Date	26/07/2019

SDS Version Summary

Version	Date of Update	Sections Updated
4.1	04/02/2020	Acute Health (inhaled), Chronic Health, Classification, Ingredients, Physical Properties
5.1	23/12/2022	Classification review due to GHS Revision change.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit_o IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals **DSL:** Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.